



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Device application	Lightweight installation
Drilling diameter	14 mm concrete
Minimum drilling depth	78 mm
Screw diameter	10... 12 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear: 4 kN for concrete C25 4.5) Pull-out load: 2.5 kN for concrete C25 6)
Practical load capacity	Shear: 400 kg for concrete C25 4.5) Pull-out load: 250 kg for concrete C25 6)
Colour tint	Grey
Ambient air temperature for operation	-50...80 °C
Diameter	14 mm
Length	70 mm

Environment

Quantity per set	Set of 10
Sale per indivisible quantity	1
Net weight	0.0075 kg

Packing Units

Package 1 Weight	1.000 g
Package 1 Height	14.000 mm
Package 1 width	14.000 mm
Package 1 Length	70.000 mm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.