



Main

| | |
|-------------------------------------|---|
| Range | Acti 9 |
| Product name | Acti 9 DPN Vigi K |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | DPN Vigi K |
| Device application | Distribution |
| Poles description | 1P + N |
| Number of protected poles | 1 |
| Neutral position | Left |
| [In] rated current | 20 A |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |
| Breaking capacity | 6000 A Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Quality labels | VDE |

Complementary

| | |
|--|---|
| Device location in system | Outgoer |
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Magnetic tripping limit | 5...10 x In |
| Residual current tripping technology | Voltage independent |
| [Ics] rated service breaking capacity | 6000 A 100 % x Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Rated breaking and making capacity | Idm 4500 A at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Limitation class | 3 conforming to EN/IEC 61009-2-1 |
| [Ui] rated insulation voltage | 400 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON, OFF, fault trip |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 4 |
| Height | 81 mm |
| Width | 36 mm |
| Depth | 72 mm |
| Net weight | 125 g |
| Colour | White (RAL 9003) |
| Mechanical durability | 20000 cycles |
| Electrical durability | 20000 cycles |

| | |
|--------------------------|--|
| Connections - terminals | Tunnel type terminal phase 1...25 mm ² rigid Tunnel type terminal neutral 1...16 mm ² rigid Tunnel type terminal phase 1...16 mm ² flexible Tunnel type terminal neutral 1...10 mm ² flexible |
| Wire stripping length | 15 mm for top or bottom connection |
| Tightening torque | 2 N.m top or bottom |
| Earth-leakage protection | Integrated |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 61009-2-1 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 |
| Overvoltage category | III conforming to IEC 60364 |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 250 A conforming to EN/IEC 61009-2-1 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -30...70 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 223 g |
| Package 1 Height | 4 cm |
| Package 1 width | 8.4 cm |
| Package 1 Length | 10 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 1.396 kg |
| Package 2 Height | 11 cm |
| Package 2 width | 9 cm |
| Package 2 Length | 26 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 54 |
| Package 3 Weight | 13.111 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts product |