# ETK10150E

Ultra - installation trunking - 101 x 50 mm - plastic - white - 2 m





Main	
Product or component type	Installation trunking
Colour tint	White (RAL 9010)
Quantity per set	16 m
Type of packing	Protective foil

#### Complementary

Compartment partitioning	1 compartment
Trunking dimension	101 x 50 mm
Device composition	Front cover Trunking base
Trunking material	Plastic
Front opening size	75 mm
Fixing mode	Screw-fixed Pre-punched fixing hole 230 mm
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	101 mm
Width	50 mm

## Environment

Ambient air temperature for operation	-560 °C
Environmental health and issues	Cadmium free Lead free
IP degree of protection	IP40
IK degree of protection	IK07
Standards	EN 50085-1:2005 EN 50085-2-1:2006

### **Packing Units**

Package 1 Weight	1970.000 g
Package 1 Height	50.000 mm
Package 1 width	100.000 mm
Package 1 Length	2010.000 mm

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile