



Main

Range of product	Mureva Styl
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Schuko
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Flush Surface
Rated current	16 A
Number of power socket outlets	1
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	PP (polypropylene) PC (polycarbonate) Brass
Fixing mode	By screws
Clamping connection capacity	1...2.5 mm ² for rigid cable(s) 1...2.5 mm ² for stranded cable(s) 1...2.5 mm ² for flexible cable(s)
Wire stripping length	13 mm
Height	71 mm
Width	71 mm
Depth	50 mm
Chemical and detergent products resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Quality labels	AENOR EAC
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile