



### Main

Range of product	Resi9
Product or component type	Switch disconnecter
Device short name	Resi9 SWITCH
Poles description	3P
Standards	IEC 60669-2-4

### Complementary

[Ie] rated operational current	63 A at 400 V AC 50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz
Network frequency	50/60 Hz
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	80 mm
Width	54 mm
Depth	85 mm
Net weight	0.21 kg
Mechanical durability	2500 cycles
Electrical durability	2500 cycles
Connections - terminals	Tunnel type terminals (top or bottom) - 1...35 mm <sup>2</sup> - rigid Tunnel type terminals (top or bottom) - 1...25 mm <sup>2</sup> - flexible

### Environment

Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...80 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---