



Main

Range name	Sedna Design & Elements
Range	Sedna
Device application	Control
Product or component type	Switch
Function	2-circuits
Delivery form	Mechanism with fixing frame
Rated current	10 AX at 250 V AC
Colour	White
Colour code	RAL 9003

Complementary

Load type	1 lamp integrated ballast (100 W)
Kind of terminals	Screwless terminals
Targeted channel	Professional
Accessory / separate part type	Claw and screw for mechanism
Power range	2300 W
Device mounting	Flush
Cable cross section	2.5 mm ²
Wire structure	Rigid
Wire stripping length	13 mm
Material of visible parts	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Claws, span of claws working range: 51...70 mm Claws, span of claws working range: 52...68 mm Screws
Height	73 mm
Width	73 mm
Depth	38 mm
Depth of visual part	24 mm
Net weight	0.070 kg

Environment

IP degree of protection	IP44
Conformity mark	CE
Product certifications	GOST-R
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	75 g
Package 1 Height	4.5 cm
Package 1 width	7.5 cm
Package 1 Length	7.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10

Package 2 Weight	832 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	10.621 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration