



Main

Range	Actassi
Product type	RJ45 network socket
Device presentation	Integrated one piece design
Colour tint	Wire organizer: green (ABS + PC) Connector: dark grey (ABS + PC)
Wiring Colour configuration	568 A/B
Type of packing	Individual bag
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	Initial insulation resistance: ≥ 500 MOhm at 100 V DC
AWG gauge	AWG 24...AWG 23
Durability	750 cycles
Coupling attenuation	≥ 35 dB at 30...100 MHz $\geq 75 - 20 \times \log(f)$ dB at 100...1000 MHz
Contact pins	8 pins of copper alloy and gold plated conforming to IEC 60603-7
Pulling force	50 N during 60 s
Transverse conversion loss	≥ 50 dB $\geq 68 - 20 \times \log(f)$ dB at 1...100000 kHz
Tool type	Without tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	UTP
Communication network category	5e
Supported applications	1000BASE-T
Protocols	VoIP (Voice IP) PoE+ (Power over Ethernet)
Product compatibility	RJ45 plug RJ11 plug
Transmission frequency	0...100 MHz
Type of footprint	S-One
Height	28 mm
Length	33 mm
Width	18 mm
Targeted region	Europe

Environment

Operational temperature range	-40...70 °C
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	PEP (Energy depletion)
Standards	ANSI/TIA-568-C.2 IEC 60603-7-2 ISO/IEC 11801:2011 Ed.2.2 UL 1863

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	9 g
Package 1 Height	3 cm
Package 1 width	2 cm
Package 1 Length	4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	149 g
Package 2 Height	6.5 cm
Package 2 width	13 cm
Package 2 Length	18.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	320
Package 3 Weight	5.518 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------