



Main

| | |
|---------------------------|-----------------------|
| Range of product | Acti 9 |
| Product name | Acti 9 iPC |
| Product or component type | Modular socket-outlet |
| Device short name | IPC |
| Poles description | 2P + E |



Complementary

| | |
|--------------------------------|--|
| [In] rated current | 16 A |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Mounting mode | Fixed |
| Mounting support | Symmetrical DIN rail |
| 9 mm pitches | 5 |
| Height | 81 mm |
| Width | 45 mm |
| Depth | 55 mm |
| Net weight | 100 g |
| Colour | White |
| Connections - terminals | Tunnel type terminal1 cable(s) 1...6 mm ² flexible Tunnel type terminal1 cable(s) 1...10 mm ² rigid |
| Wire stripping length | 13 mm |
| Tightening torque | 1.2 N.m |

Environment

| | |
|---------------------------------------|--|
| Standards | VDE 0620 UNE 20315-1-1 |
| Quality labels | EAC KEMA VDE |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| IK degree of protection | IK03 |
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...80 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |

| | |
|----------------------------|---|
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |