



### Main

Range of product	Renova
Range	Renova
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2P + E
Device presentation	Insert with central plate
Colour tint	Black (NCS S 9000-N)
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

### Complementary

Number of power socket outlets	1
Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC/ABS
Fixing mode	By screws and claws
Diameter	71 mm
Embedding depth	28 mm
Projecting depth	15 mm

### Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004
Product certifications	SEMKO FIMKO
IP degree of protection	IP20 also with visual parts removed

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	67 g
Package 1 Height	4 cm
Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	394 g
Package 2 Height	8.5 cm
Package 2 width	8.5 cm
Package 2 Length	22.5 cm

Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	6.77 kg
Package 3 Height	32.5 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins