



### Main

Range	Asfora
Product or component type	Switch
Device presentation	Complete product
Load type	Load for energy saving lamps with ballast: 100 W
Colour tint	White
Type of packing	Flow-pack

### Complementary

Device mounting	Flush
Switch function	1-pole 1-way
Number of rocker	2
Power range	2300 W
Rated current	10 AX at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...70 mm
Height	83 mm
Width	83 mm
Depth	43.0 mm
Projecting depth	15 mm
Net weight	0.0771 kg

### Environment

Standards	IEC 60669-1
Product certifications	VDE
Quality labels	CE
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	77.6 g
Package 1 Height	4 cm
Package 1 width	8.2 cm

Package 1 Length	8.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	852.33 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.7 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	10.764 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------