



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Drilling diameter	10 Mm concrete 9 mm ALC concrete
Minimum drilling depth	50 mm
Screw diameter	5...7 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear: 1.4 kN for concrete C25 4.5) Pull-out load: 1 kN for concrete C25 6) Shear: 0.4 kN for low density concrete 500 and expanded clay 4.5) Pull-out load: 0.15 kN for low density concrete 500 and expanded clay 6)
Practical load capacity	Shear: 30 kg for solid brick 4.5) Shear: 140 kg for concrete C25 4.5) Pull-out load: 100 kg for concrete C25 6) Pull-out load: 15 kg for solid brick 6)
Colour tint	Blue
Ambient air temperature for operation	-50...80 °C
Diameter	10 mm
Length	45 mm

Environment

Quantity per set	Set of 100
Sale per indivisible quantity	10

Packing Units

Package 1 Weight	3.000 g
Package 1 Height	87.000 mm
Package 1 width	132.000 mm
Package 1 Length	94.000 mm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.