ETK40340

Ultra - distribution trunking - 40 x 40 mm - PVC - white - 2 m





Main	
Product or component type	Distribution trunking
Device application	Cable distribution
Colour tint	White (RAL 9010)
Quantity per set	36 m

Complementary

Plastic 1 compartment
1 compartment
'
Pre-punched fixing hole 230 mm Power cable: screw-fixed
PVC (polyvinyl chloride)
2000 mm
40 mm
40 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-560 °C
Environmental health and issues	Lead free Cadmium free
Standards	EN 50085-1:2005 EN 50085-2-1:2006

Packing Units

Package 1 Weight	370.000 g	
Package 1 Height	40.000 mm	
Package 1 width	40.000 mm	
Package 1 Length	2000.000 mm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile