



### Main

Range name	Sedna Design & Elements
Range	Sedna
Function	Socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Flow-pack
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Colour	White
Colour code	RAL 9003
Quantity per set	1 piece

### Complementary

Power range	3680 W
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm <sup>2</sup>
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range: 52...69 mm Claws, span of claws working range: 52...69 mm
Height	73 mm
Width	73 mm
Depth	41 mm
Depth of visual part	29 mm
Net weight	0.069 kg

### Environment

Standards	IEC 60884-1
Conformity mark	CE EAC
Product certifications	VDE AENOR
IP degree of protection	IP20

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	79.5 g
Package 1 Height	4 cm
Package 1 width	8 cm
Package 1 Length	8.1 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	796 g
Package 2 Height	9.5 cm
Package 2 width	18.6 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	10.215 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>