



## Main

Range name	Sedna
Function	Socket-outlet
Delivery form	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A at 250 V AC
Socket additional information	Lid
Colour code	RAL 9003

## Complementary

Power range	3680 W
Kind of terminals	Screw terminals
Terminal capacity	2 cable(s) 2.5 mm <sup>2</sup>
Wire structure	Flexible Rigid
Wire stripping length	13 mm
Material of visible parts	ASA + PC
Surface finish	Glossy
Fixing mode	Screws 5.2...6.9 Mm By screws and claws, span of claws working range:
Height	71 mm
Width	71 mm
Depth	47.3 mm
Depth of visual part	16 mm
Net weight	0.073818 kg

## Environment

Standards	IEC 60884-1
Product certifications	GOST-R
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	75.5 g
Package 1 Height	4.7 cm
Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Package 2 Weight	837.75 g
Package 3 Weight	10.726 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------