



Main

Range of product	Resi9
Product or component type	Switch disconnecter
Device short name	Resi9 SWITCH
Poles description	1P
Standards	IEC 60669-2-4

Complementary

[Ie] rated operational current	25 A at 230 V AC 50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz
Network frequency	50/60 Hz
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	76 mm
Width	18 mm
Depth	82 mm
Net weight	0.075 kg
Mechanical durability	5000 cycles
Connections - terminals	Tunnel type terminals (top or bottom) - 1...35 mm ² - rigid Tunnel type terminals (top or bottom) - 1...25 mm ² - flexible

Environment

Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
