



Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit
Mounting plate description	Slotted

Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	6
Total number of 18 mm modules	6
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Provided equipment	1 marking kit
Type of front cover	Transparent
Power dissipation in W	11 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	159 mm
Height	200 mm
Depth	112 mm
Internal depth	56 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Environment

Standards	IEC 60529 IEC 60695-2-1 IEC 670 EN 50102 IEC 60439-3 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	515 g
Package 1 Height	11.15 cm
Package 1 width	16 cm
Package 1 Length	20 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	7
Package 2 Weight	4.015 kg
Package 2 Height	34 cm
Package 2 width	22 cm
Package 2 Length	41 cm
Unit Type of Package 3	P12
Number of Units in Package 3	168
Package 3 Weight	108.36 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------