



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	Socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Flow-pack
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Socket additional information	Lid
Colour	White
Colour code	RAL 9003
Quantity per set	1 piece

Complementary

Power range	3680 W
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range: 52...69 mm Claws, span of claws working range: 52...69 mm
Height	73 mm
Width	73 mm
Depth	50 mm
Depth of visual part	29 mm
Net weight	0.070 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE EAC
Product certifications	VDE AENOR
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile