



Main

Range	Sedna
Range of product	Sedna
Device short name	SBD200LED
Product or component type	Dimmer
Device application	Control

Complementary

Dimmer type	Universal
Dimmer control	Rotary push type
Control type	Rotary push type
Switch function	1-pole 2-way
Load type	Incandescent lamp 230 V halogen lamp LED lamp Low voltage halogen lamp with ferromagnetic transformer Low voltage halogen lamp with electronic transformer
Power range	Halogen lamp: 4...400 W Incandescent lamp: 4...400 W LED lamp: 4...40 W (RL LED mode) LED lamp: 4 W...200 VA (RC LED mode) Low voltage halogen lamp with electronic transformer: 4...400 W Low voltage halogen lamp with ferromagnetic transformer: 4 W...400 VA
[Ue] rated operational voltage	230 V AC 50/60 Hz
Rated current/voltage	10 A at 230 V AC
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Clamping connection capacity	1 x 2.5 mm ² for solid or flexible with sleeve cable(s) 2 x 1.5 mm ² for solid or flexible with sleeve cable(s)
Colour	Graphite
Material	Thermoplastic: central plate Thermoplastic: knob
Device mounting	Flush
Fixing mode	By screws
Embedding depth	29 mm
Height	71 mm
Width	71 mm
Depth	51 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	5...95 %
IP degree of protection	IP20 also with visual parts removed

Packing Units

Package 1 Weight	98.000 g
Package 1 Height	52.000 mm
Package 1 width	71.000 mm
Package 1 Length	71.000 mm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins