



### Main

Range	Asfora
Product or component type	Socket-outlet
Outlet poles configuration	2 x 2P
Device presentation	Complete product
Colour tint	White
Type of packing	Flow-pack

### Complementary

Socket number	2
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	11 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ASA + PC: central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws54...72 mm
Height	123 mm
Width	83 mm
Depth	46 mm
Projecting depth	23 mm
Quantity per set	1

### Environment

Standards	IEC 60884-1
Product certifications	B UKR
IP degree of protection	IP20

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins