



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	Socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Flow-pack
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Socket additional information	Shuttered
Colour	Anthracite
Colour code	RAL 7021
Quantity per set	1 piece

Complementary

Power range	3680 W
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Painted
Fixing mode	Screws or claws, span of claws working range: 52...69 mm Claws, span of claws working range: 52...69 mm
Height	73 mm
Width	73 mm
Depth	41 mm
Depth of visual part	29 mm
Net weight	0.069 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE EAC
Product certifications	VDE AENOR
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	71 g
Package 1 Height	4.5 cm
Package 1 width	7.5 cm
Package 1 Length	7.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	798 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	10.22 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile