SDN3100321

Sedna - single socket outlet, side earth - 16A IP44 shutter, lid, wo frame white



Main	
Range name	Sedna
Function	Socket-outlet
Delivery form	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A at 250 V AC
Socket additional information	Lid

Complementary

Complementary		
Power range	3680 W	
Kind of terminals	Lift terminals	
Terminal capacity	2 cable(s) 2.5 mm²	
Wire structure	Flexible Rigid	
Wire stripping length	13 mm	
Material of visible parts	ASA + PC	
Surface finish	Glossy	
Fixing mode	Claws, span of claws working range: 5269 mm Screws	
Height	71 mm	
Width	71 mm	
Depth	49.3 mm	
Depth of visual part	18 mm	
Net weight	0.077032 kg	

Environment

Standards	IEC 60884-1
Product certifications	GOST-R
IP degree of protection	IP44

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	79.667 g	
Package 1 Height	5.4 cm	
Package 1 width	7.1 cm	
Package 1 Length	7.1 cm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Weight	881 g	
Package 2 Height	9.5 cm	
Package 2 width	18.5 cm	
Package 2 Length	27.5 cm	
Unit Type of Package 3	S04	

Number of Units in Package 3	120
Package 3 Weight	11.238 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Compliant EEU RoHS Declaration
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Wallanty	Warranty	18 months
----------	----------	-----------