



### Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

### Complementary

Type of installation	Outdoor
Total system power	20 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	R <sub>a</sub> =80
Luminous flux	2000 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour	Black
Beam angle	110 °
Shape	Rectangular
Height	163.4 mm
Width	121.4 mm
Depth	26.0 mm
Net weight	530 g

### Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
IK degree of protection	IK05
Ambient air temperature for operation	-30...45 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	560 g
Package 1 Height	17.2 cm
Package 1 width	17.2 cm
Package 1 Length	17.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Weight	11.641 kg

Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Weight	198.256 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins