



Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2P + E with shutters
Device presentation	Complete product
Socket additional information	Shuttered
Colour tint	White
Type of packing	Flow-pack

Complementary

Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ABS + PC: central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...69 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	10 mm
Quantity per set	1
Net weight	0.081 kg

Environment

Standards	IEC 60884-1
Product certifications	TSE VDE AENOR
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins