



Main

Aesthetic name	System M M-Smart M-Arc M-Elegance M-Star M-Plan M-Plan glass
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Outlet standard	German
Socket additional information	With hinged lid

Complementary

Outlet poles configuration	2P + E
Wiring device mounting	Flush
Fixing mode	By screws and claws
[In] rated current	16 A
[Ue] rated operational voltage	250 V
Colour tint	White glossy
Colour code	RAL 1013
Connections - terminals	Screwless terminals
Material	Polycarbonate glossy

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	102 g
Package 1 Height	5.3 cm
Package 1 width	7.6 cm
Package 1 Length	7.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Weight	5.51 kg
Package 2 Height	18.5 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------