



Main

Range	Asfora
Product or component type	Switch
Device presentation	Mechanism with fixing frame
Load type	Load for energy saving lamps with ballast: 100 W
Colour tint	Cream
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Switch function	1-pole 2-way
Number of rocker	1.0
Power range	2300 W
Rated current	10 AX at 250 V AC
Connections - terminals	Screwless terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...70 mm
Height	71 mm
Width	71 mm
Depth	43.0 mm
Projecting depth	15 mm
Net weight	0.05975 kg

Environment

Standards	IEC 60669-1
Product certifications	TSE VDE NF
Quality labels	CE
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins