


MOON LED

Product Group: High-bays



Images for the product family and options:



Description: A budget LED high-bay luminaire with symmetric reflector for high mounting applications
Reflector: anodized aluminum, symmetric
Diffuser: tempered glass, clear
Body: die-cast aluminum, dark grey finish

General data: Mains voltage: 220-240V, 50-60Hz
Power factor: >0,97
Light source: LED
Light source included: Yes
Light distribution type: Direct
LED lifetime, h: 30000/L70B50
Operating temperature range, °C: ta -30...+40
Protection class IEC: I
Ingress protection code: IP65
Mechanical impact resistance: IK06
EEC: A+

Installation: Suspended. Supplied with suspension hook and out-going cable for easy mounting. Cable, 0.2m, 3x0.75mm²

Environment: Indoor


Application: Industry, warehouse, hall

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Moon LED1x10000 D764 T740	435	435	190	10000	100,0	100	70+	4000	2,06
Moon LED1x20000 D765 T740	565	565	240	20000	200,0	100	70+	4000	4,50

* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

Available options:

T740 Colour temperature 4000K, CRI 70+



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²
Description: Quick and easy to connect power supply and luminaire cables connector - IP66/IP68, 3x1.5mm², 400V/16A, 1pcs



Product: Suspension MTG KIT - Saturn LED 1.5m
Description: Suspension kit for Saturn LED high-bay, 1.5 meter
Product: Suspension MTG KIT - Saturn LED 3.0m
Description: Suspension kit for Saturn LED high-bay, 3.0 meter
Product: Suspension MTG KIT - Saturn LED 5.0m
Description: Suspension kit for Saturn LED high-bay, 5.0 meter